



- Deepfreezers





DEEPFREEZER'S SPECIFICATIONS

Single and Twin Door Deepfreezers

CRYSTAL deepfreezers are available as single door and twin door units. All CRYSTAL deepfreezer models offer a choice of desirable colours like swan cream and white in PCM and beige new, white grey and dark grey in VCM. PCM models use stucco sheet while VCM models use SS sheet.

Modern Rounded Look

The rounded shape on the inside and the outside of the deepfreezer not only give it a modern look but also provides more contact area between the inner cabinet and the copper pipe, thus increasing the performance of the freezer.

Even Refrigeration

The cooling coil winds around the freezer compartment on all sides, thus ensuring perfectly uniform and constant low temperature throughout the freezing compartment. Thus specialized coil is made of copper and is absolutely corrosion-proof.

Rust & Scratch Proof

CRYSTAL deepfreezers are available with inner lining made of either aluminum sheet or new SS sheet. They have a rust and scratch proof surface and a stainless and odorless lining.

Easily Opened Lid

CRYSTAL uses a special rubber gasket with six small holes, maintaining the exact temperature inside and enabling the lid to open easily.

Special Features

New handle with strong grip, increased pipe size to reduce compressor head pressure, greater thickness of the foam (50 mm), improved freezer serviceability, thermoformed top frame instead of extrusion, new light cover design, rounded hinge cover and specially designed wheels which make the movement of the deepfreezer easy.

New Compressor

CRYSTAL deepfreezer is powered by the world's No. 1 compressor, Danfoss (Germany). This low-noise compressor is extremely silent and well prepared to face Pakistani electrical outages. It remains functional on voltages as low as 170 volts and has an upper limit of 250 volts.

Progressive Products, Absolute Guarantee

For complete customer satisfaction, all CRYSTAL deepfreezers are backed by a 2-year compressor and 1 year parts guarantee.

We'll Be There When You Need Us

Excellent hassle-free service is only a phone call away. Just call the PEL Service Centre in your city and technician will be at your doorstep the same day.

Description	Unit	Models				
		PDF-175	PDF-275	PDF-370	PDF-370 TWIN	PDF-410 TWIN
Capacity	Litres	162	260	350	327	370
Nominal tension	V	220	220	220	220	220
Frequency	Hz	50	50	50	50	50
Rated Capacity	W	104	127	158	146	158
Total current	Amps	1.20	1.10	1.80	1.30	1.80
Adjustable thermostat	-	Yes	Yes	Yes	Yes	Yes
Refrigerant R-12	Kg	0.250	0.250	0.250	0.270	0.275
Overall Dimensions	H (mm)	860	860	860	860	860
	W (mm)	672	940	1200	1200	1320
	D (mm)	600	600	600	600	600
Gross weight	Kg	54	60	68	78	80

Design and specifications are subject to change without prior notice